

MJV SERIES 550-770 kVA

TECHNICAL SPECIFICATIONS



GENERATOR GROUP		MJV0550	MJV0660	MJV0700	MJV0770
MODEL					
Stand By Power	kVA	550	660	700	770
	kW	440	528	560	616
Prime Power	kVA	500	600	636.3	700
	kW	400	480	509.1	560
DIESEL ENGINE		VOLVO PENTA			
BRAND		TAD1641GE	TAD1642GE	TWD1643GE	TWD1645GE
Model					
Engine Power - Stand By	kW	473	554	596	654
Engine Power - Prime	kW	430	503	536	588
Engine Speed (rpm)		1500	1500	1500	1500
Number of Cylinder		6 - In Line	6 - In Line	6 - In Line	6 - In Line
Displacement (lt)		12.78	12.78	12.78	12.78
Bore x Stroke (mm)		131x158	131x158	131x158	131x158
Compression Rate		18.1:1	18.1:1	18.1:1	18.1:1
Governor Type		Electronic	Electronic	Electronic	Electronic
Induction		TurboCharged-Intercooler	TurboCharged-Intercooler	TurboCharged-Intercooler	TurboCharged-Intercooler
Combustion System		Direct Injection	Direct Injection	Direct Injection	Direct Injection
Cooling System		Water Cooled	Water Cooled	Water Cooled	Water Cooled
Lubrication Oil Capacity (lt)		36	36	36	36
Coolant Capacity (lt)		44	44	44	44
Fuel Tank Capacity (lt)		1050	1050	1050	1050
Fuel Consumption lt / h	100% of Prime Power	101.8	118.5	127.0	133.5
	75% of Prime Power	75.2	87.6	93.9	99.4
	50% of Prime Power	50.9	58.4	62.5	68.4
ALTERNATOR					
Output Voltage (V)		400/230			
Power Factor		0.8			
Number of Poles		4			
Frequency (Hz)		50			
Voltage Regulation		±%0,5			
Connection Type		Star			
DIMENSIONS & WEIGHT		MJV0550	MJV0660	MJV0700	MJV0770
Canopy Dimensions	mm (WxDxH)	1970x5000x2500	1970x5000x2500	1970x5000x2500	1970x5000x2500
Canopy Weight	kg	3960	4165	4640	4690
Open Dimensions	mm (WxDxH)	1970x5000x2250	1970x5000x2250	1970x5000x2250	1970x5000x2250
Open Weight	kg	3420	3625	4100	4150

Aytemiz-Makelsan reserves the right to make changes in model, specification, color, equipment and accessories without prior notice.

N/A: These dimensions and weights may change depending upon the characteristics of the project.